



# PRODUCT PROFILE

## DR STAINLESS STEEL DRAINAGE PUMP

### ZEN-DRSTEEL55MA



Drainage pump in 304SS, complete with twin mechanical seals in oil bath and through motor cooling which guarantees motor cooling even at low pumping levels. Strainer base can be converted to allow pumping down to 5mm for special applications.

#### The pump is characterised by:

- For clean water containing solids up to 12mm
- For draining rooms or emptying tanks
- For water from ponds, streams or pits and for rainwater collection.
- Max head 12.4 m
- Max flow 300 l/min

#### Electrical data:

Rated voltage:	240V
Rated output:	0.55 kW
Mains frequency:	50 Hz
Current:	4.3 amps
Capacitor:	14uF
Motor duty:	Continuous
Motor type:	Asynchronous
Motor protection:	In-built thermal overload
Ingress protection:	IP 68
Insulation class:	F
Power cable length:	10 m
Net weight:	7.7 kg
Dimensions:	215Ø x 335H (mm)

#### Liquid:

Clean water temperature range: 2-35°C

#### Materials:


Pump casing, body:	Chrome-nickel steel AISI 304
Strainer, Impeller:	Chrome-nickel steel AISI 304
Shaft:	AISI 420
Seal (x2):	Silicon carbide/graphite alumina mechanical seals in oil chamber
Seal (x1):	V-ring in direct contact with the liquid

#### Installation:

Maximum operating temperature:	40°C
Maximum immersion depth:	10m
Outlet:	1½" BSPF

**2 Year Zenit Pump Warranty - Parts & Labour**

ZEN-DRSTEEL55MA



Distributed by White International Pty Ltd  
A.B.N. 48 000 119 380  
PO BOX 304 MILPERRA LPO NSW 2214  
Ph: 02 9783 6000 Fax: 02 9783 6001  
HOTLINE: 1300 783 601 FAXLINE: 02 9783 6003

Distributed by White International NZ Ltd  
138 Hugo Johnston Dr, Penrose, Auckland  
PO BOX 12704, PENROSE, AUCKLAND  
Ph: 09 579 9777 Fax: 09 579 7775  
HOTLINE: 0800 509 506 FAXLINE: 0800 804 344  
ZEN-DRSTEEL55MA\_DS\_110707