

PRODUCT DATA SHEET

NXT FLEXI SOLAR-75

811614

PRODUCT DETAILS

The Bianco NXT Flexi-Solar pump controller is a variable speed drive designed for three-phase asynchronous motors and permanent magnet synchronous motors.

High-voltage DC power from a solar array is converted into AC power to drive the pump. When the solar energy drops, the controller can automatically switch to a backup AC power source, such as generator or battery storage

The incoming power source can be DC, AC or a combination of both.

APPLICATIONS

- Off-grid pumping
- Combining Solar DC and locally generated AC power to reduce running costs of ICE power generation
- Powering standard 3 phase pumps with asynchronous motors

FEATURES

- Hybrid DC/AC controller
- Pump protection and control
- Motor soft starting
- Speed control
- Fault monitoring and Protection
- Multi pump control. 1 master and up to 5 auxiliarly controllers
- Optimised pump performance Solar Maximum Power Point Tracking (MPPT)



TECHNICAL DATA

MAXIMUM DC VOLTAGE	800V DC
STARTUP DC VOLTAGE	220V DC
LOWEST DC VOLTAGE	200V DC
RECOMMENDED MPPT DC VOLTAGE	400 - 750V DC
BEST DC WORKING VOLTAGE	560V DC
INPUT AC VOLTAGE	280 - 440V 3 phase
AC INPUT FREQUENCY	50 / 60Hz
INPUT CIRCUITS	2 pairs MC4

OUTPUT VOLTAGE	415V 3 phase
RATED CURRENT	17.0 amps
POWER OUTPUT	7.5 kW nominal
PROTECTION CLASS	IP65
WORKING TEMPERATURE	20 to 60° C ambient
COOLING	Air Cooled
EXTERNAL DIMENSIONS	396W x 371D x 184H
WEIGHT (KG)	13.5 kg



