



CARAVANS  
& RV'S



CAMPING AND  
RECREATION



HOME  
BACKUP



MARKET STALLS  
MOBILE BUSINESS



OUTDOOR  
EVENTS



DIY  
WORKSHOP



'Pure Sine Wave' output.  
Total harmonic distortion <3%

Suitable for powering sensitive  
electronics and medical devices



## PRODUCT DETAILS

The Welling and Crossley P9000Si is a Smart Silent Inverter type generator - the ideal companion for camping or outdoor adventures, home backup or general home handyman tasks. The highly efficient Euro 5 certified motors and advanced inverter technology provides stable, clean power for sensitive electronics. The intelligent idle control optimises fuel efficiency and reduces noise. The P9000Si is fitted with a retractable handle and wheels for ease of transportation and storage. Enjoy the convenience of a full-colour LCD display and quick-charge USB ports next time you're off the grid.

## APPLICATIONS

- Plentiful power for off-grid living with all the comforts of home. Ideal as a back-up solution to keep the entire home running
- Ideal for farms, shearing plants, construction sites and hire companies.
- Best performance when providing power for steady loads with little surge or in-rush current demand

## FEATURES

- 2 x IP66 Outlets (single phase - 15 Amp)
- 1 x IP66 Outlets (single phase - 32 Amp)
- 1 x USB A 18W
- 1 x USB C 15W
- eStart, Wireless and Recoil starting.
- 2 wire start connection
- Acoustic casing with forced fan cooling
- Digital V/F/T Display (Volts, Frequency, Time)
- Low oil alarm, overload alarm, output indicator
- 2 year Welling and Crossley Warranty (battery excluded)

## TECHNICAL DATA

|                          |  |
|--------------------------|--|
| <b>MODEL</b>             | WC-P9000SI   |
| <b>MAX. AC OUTPUT</b>    | 9000W  |
| <b>RATED AC OUTPUT</b>   | 8200W Max 34.2 Amp   |
| <b>RATED MOTOR SPEED</b> | 3000rpm  |
| <b>RATED VOLTAGE</b>     | 240V AC 1 Ph / 50Hz  |
| <b>ENGINE MODEL</b>      | WC-460B: Euro 5 emissions compliant                                |
| <b>ENGINE TYPE</b>       | Single cylinder, 4 stroke, OHV, fan forced air cooled petrol motor |
| <b>IGNITION SYSTEM</b>   | Transistor   |
| <b>DISPLACEMENT</b>      | 459cc  |

|                              |                              |
|------------------------------|------------------------------|
| <b>OIL</b>                   | 1.2 litres SAE10W-30         |
| <b>SPARK PLUG</b>            | TORCH F7RTC                  |
| <b>NOISE LEVEL @ 7M</b>      | 64 dBA @ 7m                  |
| <b>FUEL TYPE</b>             | Petrol - 91 octane unleaded. |
| <b>FUEL TANK CAPACITY</b>    | 27 L                         |
| <b>FUEL CONSUMPTION</b>      | Approx 1.45 L/Hr @ 1/4 load  |
| <b>PACKAGING (L X W X H)</b> | 750 x 700 x 775mm            |
| <b>PRODUCT (L X W X H)</b>   | 670 x 735 x 755mm            |
| <b>DRY WEIGHT</b>            | 99kg                         |